

N-66-3626

MEMORANDUM  
RM-5084-NASA  
AUGUST 1966

# A BAYESIAN APPROACH TO RELIABILITY ASSESSMENT

B. L. Fox

FACILITY FORM 602	N66 36262	(ACCESSION NUMBER)
	27	(PAGES)
	CR-77910	(NASA CR OR TMX OR AD NUMBER)
	8X C	(THRU)
	79	(CATEGORY)

PREPARED FOR:

NATIONAL AERONAUTICS AND SPACE ADMINISTRATION

The RAND Corporation  
SANTA MONICA • CALIFORNIA



MEMORANDUM

RM-5084-NASA

AUGUST 1966

A BAYESIAN APPROACH  
TO RELIABILITY ASSESSMENT

B. L. Fox

N 65 36282

This research is sponsored by the National Aeronautics and Space Administration under Contract No. NASr-21. This report does not necessarily represent the views of the National Aeronautics and Space Administration.



# N O T I C E

THIS DOCUMENT HAS BEEN REPRODUCED FROM  
THE BEST COPY FURNISHED US BY THE SPONSORING  
AGENCY. ALTHOUGH IT IS RECOGNIZED THAT CER-  
TAIN PORTIONS ARE ILLEGIBLE, IT IS BEING RE-  
LEASED IN THE INTEREST OF MAKING AVAILABLE  
AS MUCH INFORMATION AS POSSIBLE.



PREFACE

The research described here was performed for the National Aeronautics and Space Administration, and deals with the APOLLO Mission Reliability Assessment Study. In this Memorandum, the author uses Bayesian analysis to specify parameters of a prior distribution for two cases: (1) reliability of a unit that either performs satisfactorily throughout a mission or does not, and (2) failure rate of a unit that fails according to the exponential distribution. Prediction of demand for spares is considered in each case. The cases can be read independently.

An estimate of reliability is the posterior mean. Alternatively, the posterior distribution can be used to obtain a (subjective) confidence interval for reliability. The posterior distribution is also useful in a decision-theoretic approach to resource allocation for maximal system reliability; such a study is planned as a sequel to the present work.

This Memorandum should be of interest to those working on reliability estimation; allocation of investment among system components to achieve maximum system reliability; and stockage applications.





SUMMARY

This Memorandum specifies the parameters of a prior distribution for two cases: the reliability of a unit that either performs satisfactorily throughout a mission or does not; and the failure rate of a unit that fails according to the exponential distribution.

Bayesian analysis is an obvious approach in estimating reliability parameters from mixed data sources such as: (1) test results; (2) information on analogous components; and (3) engineering estimates. The prior distribution, of necessity subjective, is (ideally) based on (2) and (3) alone. Test results are then merged with the prior via Bayes' rule to obtain a posterior distribution. Roughly, the spread of the prior distribution is inversely proportional to the degree of prior belief, and determines how heavily it will be weighted when combining it with test data.

A topic that most writers on Bayesian analysis avoid is how to specify the parameters of the prior distribution based on (2) and (3). We give a method for specifying these parameters that requires only information corresponding (i) to the most likely value of reliability and (ii) to the subjective odds that the error in this estimate is less than a given percent. We have computed tables of parameters of the prior distribution corresponding to these subjective inputs. These appear in the Appendix.

As an application of Bayesian analysis, we consider prediction of demand for spares in both the GO NO-GO and constant failure rate cases.



PRECEDING PAGE BLANK NOT FILMED.

-vii-

CONTENTS

PREFACE .....	iii
SUMMARY .....	v
Section	
1. SPECIFYING THE PARAMETERS OF A PRIOR DISTRIBUTION FOR RELIABILITY OF A GO NO-GO UNIT .....	1
2. SPECIFYING THE PARAMETERS OF A PRIOR DISTRIBUTION FOR FAILURE RATE .....	6
APPENDIX .....	11
REFERENCES .....	23



1. SPECIFYING THE PARAMETERS OF A PRIOR DISTRIBUTION FOR  
RELIABILITY OF A GO NO-GO UNIT

Suppose we have a unit that works with probability  $p$  but that the precise value of  $p$  is unknown. If we were totally ignorant about the value of  $p$ , then our prior belief would be reflected by a uniform distribution over  $[0,1]$ . However, intuition tells us that total ignorance is an anomaly; that is, our prior distribution is really not flat. A smooth, unimodal prior distribution having support  $(0,1)$  with peak over what we believe to be the most likely value of  $p$  seems appropriate. In addition, the beta distribution is a natural conjugate [5] prior distribution; i.e., the posterior distribution is again a beta distribution (with parameters transformed according to Bayes' rule). The beta density with positive parameters  $(a,b)$  is given by

$$(1.1) \quad \beta(p|a,b) = \begin{cases} c p^{a-1}(1-p)^{b-1}, & 0 < p < 1 \\ 0, & \text{elsewhere} \end{cases},$$

with  $c$  as a normalizing factor. The mean and variance are, respectively:

$$(1.2) \quad \mu = a/(a+b),$$

$$(1.3) \quad \sigma^2 = ab/[(a+b)^2(a+b+1)],$$

and, for  $a, b > 1$ , there is a unique mode at

$$(1.4) \quad \theta = (a-1)/(a+b-2).$$

After observing test data, say a sample with  $m$  successes and  $n$  failures, the posterior density is  $\beta(p|a+m, b+n)$  from the Bayes' rule relation: posterior density = prior density  $\times$  likelihood function  $\times$  a normalizing factor independent of  $p$ . As more test data are observed, the posterior distribution is updated. (The updating procedure is valid

only if all units are stochastically identical. If, for example, design changes are made, as a result of failure mode analysis, a new prior distribution should be constructed from scratch).

It remains to specify the parameters (a,b). The procedure we give is heuristic and, while not the simplest mathematically, uses information that corresponds to subjective notions.\* For example, one is less likely to have a feel for the variance of the prior distribution than for the error in his estimate of the most likely value of p. Of course, if we were interested in psychological consistency, we could ask for an estimate of the variance as well -- but we shall ignore such considerations here. If the designer/engineer being asked these questions has seen any test data, it is probably impossible for him to ignore them. Therefore, in this case, it is suggested that the prior distribution be based on all information the designer knows. On the other hand, if the designer has not seen any test data, this is all to the good; test results are then accounted for in the posterior distribution. Whenever possible, the parameters of the prior distribution should be specified before any tests are performed.

Suppose that our subjective assessment of the most likely value\*\* of p is  $\hat{p}$ ; then we set

$$(1.5) \quad (\hat{a}-1)/(\hat{a}+\hat{b}-2) = \hat{p}.$$

---

\* For example, if  $\hat{\mu}$  and  $\hat{\sigma}$  were subjective estimates of the mean and variance, respectively, of the prior distribution, then solving the equations (1.2) and (1.3) yields

$$\hat{a} = \hat{\sigma}^{-2} \hat{\mu}^2 (1-\hat{\mu}) - \hat{\mu}$$

$$\hat{b} = \hat{\sigma}^{-2} \hat{\mu} (1-\hat{\mu})^2 - (1-\hat{\mu}).$$

\*\* The analysis of the case where one estimates the mean rather than the mode is analogous. We give no details for the former case, except that numerical results for both cases are given in Tables 1 and 2 in the Appendix.

Next, we ask what odds we would give that the true value of  $p$  lies in  $(\hat{p}-k\hat{p}, \hat{p}+k\hat{p})$ , where  $0 < k < 1$ . For example, if  $k = .1$ , then we ask what the chance is that the error in our estimate is less than 10 percent. Suppose that the subjective odds are  $x$  to  $y$ ; then, setting  $v = x/(x+y)$ , we have

$$(1.6) \quad \int_{\hat{p}-k\hat{p}}^{\hat{p}+k\hat{p}} \beta(p|\hat{a},\hat{b}) dp = v.$$

Thus, to find  $\hat{a}$  and  $\hat{b}$ , it suffices to specify  $\hat{p}$ ,  $k$ , and  $v$ . If the views of several people are solicited, it is suggested that the decision-maker take weighted averages, the weights  $\{\alpha_i\}$  depending on the technical backgrounds and personalities of the people involved. Some may be conservative in their estimates, while others are optimistic. It is suggested that in asking the questions the decision-maker fix the value of  $v$ . If person  $i$  responds  $(\hat{p}_i, k_i)$ , then  $\hat{p} = \sum \alpha_i \hat{p}_i / \sum \alpha_j$  and  $k = \sum \alpha_i k_i / \sum \alpha_j$ .

Equations (1.5) and (1.6) can be resolved by using the tables of the incomplete beta function [3], but to expedite matters we have provided a table of  $(\hat{a}, \hat{b})$  in the Appendix corresponding to selected values of  $(u, v, k)$ , where  $u = \hat{p}$ .

Defining

$$(1.7) \quad \phi(t; u, v, k) = v - \frac{\int_{u(1-k)}^{\min(1, u(1+k))} \frac{u(t-1)}{p^{1-u}} (1-p)^{t-1} dp}{\int_0^1 \frac{u(t-1)}{p^{1-u}} (1-p)^{t-1} dp}$$

and

$$(1.8) \quad \phi[g(u, v, k); u, v, k] = 0,$$

it follows from (1.5) and (1.6) that

$$(1.9) \quad \hat{b} = g(\hat{p}, v, k),$$

$$(1.10) \quad \hat{a} = [\hat{p}(\hat{b}-2) + 1]/(1-\hat{p}).$$

A uniform prior is suggested, if there is not enough prior information to quantify sensibly; however, it is felt that introspection will generally reveal the contrary.

In base stockage application [2], appropriate levels of spares inventory must be determined. To provision spares properly, an estimate of the demand distribution is required. For this, the Poisson approximation may be useful. Assuming that  $p$  is near one and the sample size  $n$  (say, aircraft landings or space vehicle launchings) is large, the probability of  $k$  failures,\* corresponding to demands for spares of a given type, is closely approximated by

$$(1.11) \quad f(k|p, n) = [n(1-p)]^k e^{-n(1-p)} / k!.$$

Removing the conditioning on  $p$ , the demand distribution is

$$(1.12) \quad g(k|a, b, n) = \int_0^1 f(k|p, n) \beta(p|a, b) dp.$$

An approximation to  $g(k|a, b, n)$  is obtained by using the mean of the prior distribution  $[a/(a+b)]$  in place of  $p$  in (1.11). We do not know how good this approximation is.

---

\*We assume that the failure distribution over successive missions is geometric (i.e., no memory). The part in question is assumed stressed (used) exactly once per mission -- or, with obvious modifications, twice per mission. If it is stressed continuously, the results of Sec. 2 can be applied; of course, if all missions have the same length, we get a reduction back to the case considered here.



If the distribution of  $n$ , say  $\phi(n)$ , is known,<sup>\*</sup> then the distribution of the number of failures is

$$(1.13) \quad h(k|a,b) = \sum_n g(k|a,b,n) \phi(n).$$

To the author this indirect route to demand prediction seems preferable to a direct attack because the former is more physically motivated.

A device sometimes used is to inflate the estimate of demand deliberately in order to cause a larger provisioning of buffer stocks, with the object of reducing the incidence of stockouts due to demand fluctuation. The author feels that the approach outlined in the next paragraph is more rational.

With an unbiased estimate of demand, the proper inventory level can be determined by a decision-theoretic approach. Let  $L(k,s)$  be the loss when  $k$  units are demanded and  $s$  units are stocked.<sup>\*\*</sup> The minimal expected loss  $L^0$  is

$$(1.14) \quad L^0 = \min \sum_{k=0}^{\infty} L(k,s) h(k|a,b).$$

Minimizing  $L(\bar{k},s)$ , where  $\bar{k}$  is the estimate of mean demand, may be grossly incorrect.

---

<sup>\*</sup>Predicting  $n$  via a Bayesian approach -- perhaps in conjunction with spectral analysis of time series -- may be appropriate. This involves simply one more conditioning-unconditioning in (1.13). Since the values of  $n$  over successive time periods may be autocorrelated, spectral analysis may be useful in finding a suitable parametric form for the distribution of  $n$ . For a treatment of spectral analysis, see Yaglom [6].

<sup>\*\*</sup>For example,

$$L(k,s) = c_1 s + c_2 \max(0,s-k) + c_3 \max(0,k-s),$$

where  $c_1$  is the unit purchase cost,  $c_2$  is the unit holding cost, and  $c_3$  is the unit stockout cost.

2. SPECIFYING THE PARAMETERS OF A PRIOR DISTRIBUTION FOR  
FAILURE RATE

Suppose that a unit has constant failure rate  $\theta$ , fixed but unknown. We assume a (natural conjugate [5]) prior distribution with density of the form

$$(2.1) \quad g(\theta|a,b) = a^b \theta^{b-1} e^{-a\theta} / \Gamma(b),$$

where the parameters  $(a,b)$  are to be specified. Its mean and variance are:

$$(2.2) \quad \mu = b/a,$$

$$(2.3) \quad \sigma^2 = b/a^2,$$

respectively. There is a unique mode at  $(b-1)/a$ ,  $b \geq 1$ , but it is felt that the mean time to failure is more amenable to subjective assessment in this case.

If the subjective estimate of the mean time to failure is  $\hat{v}$ , then using (2.2) we set

$$(2.4) \quad \hat{b}/\hat{a} = 1/\hat{v}.$$

Based on subjective odds, let  $v$  be the chance that the failure rate exceeds  $k/\hat{v}$ . This yields

$$(2.5) \quad \int_{k/\hat{v}}^{\infty} g(\theta|\hat{a},\hat{b}) d\theta = v.$$

Equations (2.4) and (2.5) could be resolved by using tables of the incomplete gamma function [4], but this would be a tedious job.\* To save time, for selected values of  $k$  and  $v$ , Table 3 of the Appendix provides the corresponding  $\hat{h}$ , where

$$(2.6) \quad \hat{a} = \hat{h}\hat{v},$$

$$(2.7) \quad \hat{b} = \hat{h}.$$

Defining

$$(2.8)^{**} \quad \delta(h;k,v) = v - \int_k^\infty g(\theta|h,h) d\theta,$$

$$(2.9) \quad \delta[\rho(k,v);k,v] = 0,$$

we see that

---

\* If we had used a subjective estimate, say  $\hat{\sigma}^2$ , of the variance of the prior distribution instead of (2.5), then using (2.3) and (2.4) we would have the explicit expressions

$$\hat{a} = 1/\hat{\sigma}^2$$

$$\hat{b} = 1/(\hat{\sigma}^2)^2.$$

However, it is felt that intuition for  $\sigma^2$  would be poor.

\*\* Note that

$$\int_k^\infty g(\theta|h,h) d\theta = \Gamma(h,hk)/\Gamma(h,0),$$

where

$$\Gamma(a,x) = \int_x^\infty e^{-u} u^{a-1} du.$$

A standard subroutine for computing  $\Gamma(a,x)$  is available.

$$(2.10) \quad \hat{h} = \rho(k, v).$$

In specifying the parameters of the prior distribution, we refer to the suggestions given in Sec. 1 for handling data already on hand. Failure data (except that used in forming the prior distribution) are incorporated in the posterior distribution by Bayes' rule. Having observed failures at ages  $t_1, \dots, t_k$ , and a nonfailed group with ages  $t_{k+1}, \dots, t_m$ , the posterior density<sup>\*</sup> is

$$g(\theta | a + \sum_{i=1}^m t_i, b+k).$$

This gives us our current prior distribution, which is updated as more observations are recorded. If, for example, the unit corresponding to  $t_j, j > k$ , fails at  $t'$ , updating yields

$$g(\theta | a + \sum_{i=1}^m t_i + (t' - t_j), b+k+1).$$

We now give an application to demand prediction. Suppose each of  $n$  units operates continuously until failure, at which time it is replaced instantaneously (for practical purposes) by a unit as good as new. These failures generate the demands for spares and/or repair. If each unit has constant failure rate  $\theta$ , the probability of  $k$  demands in time  $T$  is  $p(k | n\theta T)$ , where

$$(2.11) \quad p(k | \lambda) = \lambda^k e^{-\lambda k} / k!;$$

---

<sup>\*</sup>If the failure distribution were  $1 - e^{-\theta x^\alpha}$  (Weibull with known shape parameter  $\alpha$ ), replace  $t_i$  by  $t_i^\alpha, i = 1, \dots, m$ .

that is, demand is Poisson with rate  $n\theta$ . Removing the conditioning on  $\theta$ , the probability of  $k$  demands is

$$(2.12) \quad f(k|a,b,n,T) = \int_0^{\infty} p(k|n\theta T) g(\theta|a,b) d\theta.$$

If  $n$  and/or  $T$  is a random variable, we can further uncondition in a similar manner.

REMARKS. If, in fact, the life distribution of the  $j$ th unit has mean  $\mu_j$  and is nonlattice but not necessarily exponential, then [1], with

$$\theta = (1/n) \sum_{j=1}^n \mu_j^{-1} \quad \text{and } n \rightarrow \infty,$$

the stationary demand distribution becomes  $p(k|n\theta T)$ . If planned replacement takes place at age  $\tau$ , the same result holds if we replace  $\mu_j$  by the mean of the distribution truncated at  $\tau$ . (In a more sophisticated replacement policy, the planned replacement age should ideally depend on the current inventory level.) If replacement can take a significant amount of time (due, for example, to stockouts or non-negligible repair times), then the replacement time distribution should be convolved with the failure distribution, and the mean of the resulting distribution used in place of  $\mu_j$ .

For aircraft spares provisioning, a somewhat different model of the demand process may be appropriate. Suppose that a part, used only when the aircraft is flying, has constant failure rate  $\theta$  during flight\* and failure rate 0 on the ground. Let flights to the base originate from points  $\{1, \dots, m\}$ , with respective flying times  $\{w_1, \dots, w_m\}$ .

---

\* See Sec. 1 for the case where the unit is not stressed continuously during flight.

During a period of length  $T$ , let  $n_i$  be the number of flights to the base from point  $i$ . The probability of  $k$  demands during time  $T$  is

$$(2.13) \quad D(k|T) = \sum_{(k_1, \dots, k_m) \in S_k} \binom{n_i}{k_i} v_i^{k_i} (1-v_i)^{n_i-k_i},$$

where

$$(2.14) \quad v_i = 1 - e^{-\theta w_i},$$

$$(2.15) \quad S_k = \left\{ (k_1, \dots, k_m) : \sum_{i=1}^m k_i = k \right\}.$$

If all the  $v_i$ 's are near 0 and all the  $n_i$ 's are large, then we have the Poisson approximation

$$(2.16) \quad D(k|T) \approx p\left(k \mid \sum_{i=1}^m n_i v_i\right).$$

When the  $n_i$ 's and  $\theta$  are unknown, we condition and then uncondition in the usual way. If  $\theta$  has a prior distribution  $g(\theta|a,b)$  given by (2.1), then

$$(2.17) \quad p\left(k \mid \sum_{i=1}^m n_i v_i; a, b\right) = p\left(k \mid \sum_{i=1}^m n_i \left[1 - \left(\frac{a}{a+w_i}\right)^b\right]\right).$$

APPENDIX

In this Appendix we give tables of parameters of prior distributions corresponding to subjective assessments of reliability, as described in Secs. 1 and 2. The entries in the tables were computed using a program written by Mrs. Sarah Higgins, with the assistance of Robert Mobley and the author. Several test cases were computed by hand (using tables) for each program, with agreement to more than four significant figures throughout. The programs are believed to be completely debugged and are listed here for the convenience of those who may want values that are not tabulated. Tables 1 and 2 refer to Sec. 1 (beta prior). Table 3 refers to Sec. 2 (gamma prior). Asterisks in the tables indicate that the rootfinder did not locate a root within the allotted time.

-12-  
Table 1

PARAMETERS OF BETA PRIOR DISTRIBUTION FOR SELECTED VALUES  
OF u, v, AND k

A Priori Estimates			Mode		Mean	
u	v	k	a	b	a	b
.9	.5	.1	5.510	1.501	15.311	1.701
		.075	8.995	1.888	18.856	2.095
		.050	19.067	3.007	29.012	3.224
		.025	73.625	9.069	83.657	9.295
	.67	.1	11.233	2.137	21.405	2.378
		.075	18.352	2.928	28.576	3.175
		.050	39.311	5.257	49.576	5.508
		.025	*	*	163.424	18.158
	.75	.1	15.862	2.651	26.222	2.914
		.075	25.727	3.748	36.173	4.019
		.050	54.915	6.991	65.395	7.266
		.025	*	*	*	*
	.95	.1	50.195	6.466	61.012	6.779
		.075	80.184	9.798	91.500	10.167
		.050	165.106	19.234	176.772	19.641
		.025	*	*	*	*
	.99	.1	90.232	10.915	101.161	11.240
		.075	145.467	17.052	157.047	17.450
		.050	*	*	*	*
		.025	*	*	*	*
.95	.5	.1	5.910	1.258	25.348	1.334
		.075	7.954	1.366	27.555	1.450
		.050	12.165	1.588	32.062	1.687
		.025	39.270	3.014	59.320	3.122
	.67	.1	10.828	1.517	30.424	1.601
		.075	15.145	1.744	34.972	1.841
		.050	24.645	2.244	44.926	2.365
		.025	80.430	5.181	100.846	5.308
	.75	.1	14.503	1.711	34.177	1.799
		.075	20.667	2.035	40.602	2.137
		.050	34.680	2.773	55.141	2.902
		.025	112.251	6.855	132.911	6.995
	.95	.1	39.402	3.021	59.307	3.121
		.075	59.151	4.061	79.382	4.178
		.050	107.748	6.618	128.632	6.770
		.025	339.228	18.801	361.167	19.009
	.99	.1	67.365	4.493	87.362	4.598
		.075	102.944	6.366	123.272	6.488
		.050	192.310	11.069	213.312	11.227
		.025	*	*	*	*
.975	.5	.1	6.239	1.134	45.458	1.166
		.075	8.411	1.190	47.710	1.223
		.050	12.734	1.301	52.197	1.338
		.025	25.695	1.633	65.637	1.683
	.67	.1	10.689	1.248	49.979	1.282
		.075	14.711	1.352	54.111	1.387
		.050	23.166	1.568	62.790	1.610
		.025	51.772	2.302	92.096	2.361



Table 1 -- continued

A Priori Estimates			Mode		Mean	
u	v	k	a	b	a	b
.975	.75	.1	13.847	1.329	53.174	1.363
		.075	19.258	1.468	58.709	1.505
		.050	30.927	1.767	70.631	1.811
		.025	72.607	2.836	113.105	2.900
	.95	.1	33.943	1.845	73.393	1.882
		.075	48.848	2.227	88.461	2.268
		.050	83.263	3.109	123.202	3.159
		.025	223.049	6.694	263.966	6.768
	.99	.1	55.718	2.403	147.780	2.442
		.075	81.364	3.061	167.403	3.104
		.050	141.906	4.613	181.930	4.665
		.025	396.793	11.149	437.834	11.227
.99	.5	.1	6.441	1.055	105.529	1.066
		.075	8.695	1.078	107.815	1.089
		.050	13.190	1.123	112.374	1.135
		.025	26.601	1.259	125.981	1.273
	.67	.1	10.592	1.097	109.706	1.108
		.075	14.423	1.136	113.580	1.147
		.050	*	*	121.496	1.227
		.025	47.093	1.466	146.599	1.481
	.75	.1	13.437	1.126	112.565	1.137
		.075	18.381	1.176	117.556	1.187
		.050	28.610	1.279	127.882	1.292
		.025	62.041	1.617	161.611	1.632
	.95	.1	30.642	1.299	129.821	1.311
		.075	42.607	1.420	141.851	1.433
		.050	68.396	1.681	167.770	1.695
		.025	160.581	2.612	260.346	2.630
	.99	.1	48.573	1.480	147.780	1.493
		.075	68.123	1.678	167.403	1.691
		.050	111.020	2.111	210.442	2.126
		.025	269.774	3.715	369.615	3.733
.999	.5	.1	6.565	1.006	1005.572	1.007
		.075	8.871	1.008	1007.881	1.009
		.050	*	*	1012.496	1.014
		.025	27.293	1.026	*	*
	.67	.1	10.530	1.010	*	*
		.075	14.241	1.013	1013.255	1.014
		.050	*	*	1020.678	1.022
		.025	44.127	1.043	1043.174	1.044
	.75	.1	13.186	1.012	*	*
		.075	17.842	1.017	1016.857	1.018
		.050	*	*	*	*
		.025	55.493	1.055	1054.545	1.056

Table 2

PARAMETERS OF BETA PRIOR DISTRIBUTION, VARYING  $u$   
( $v = .5$ ,  $k = .2$ )

A Priori Estimate	Mode		Mean	
$u$	$a$	$b$	$a$	$b$
.990	3.049	1.021	102.089	1.031
.991	3.055	1.019	113.201	1.028
.992	3.060	1.017	127.091	1.025
.993	3.066	1.015	144.950	1.022
.994	3.072	1.013	168.762	1.019
.995	3.078	1.010	202.097	1.016
.996	3.083	1.008	252.099	1.012
.997	3.089	1.006	335.434	1.009
.998	3.095	1.004	502.103	1.006
.999	3.100	1.002	1001.997	1.003

Table 3

PARAMETERS OF GAMMA PRIOR DISTRIBUTION FOR  
SELECTED VALUES OF  $k$  AND  $v$

$k$	$v$	$\hat{h}$
.1	.5	*
	.67	.3683137
	.75	.4964839
	.90	.9725192
.5	.5	.5602821
	.67	1.4046943
	.75	2.1610065
	.90	5.3209309
.9	.5	3.2660242
	.67	*
	.75	*
	.90	*

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60

SIBFTC GRTE LIST			
C	GENERAL ROUTFINDER WRITTEN BY WERNER L. FRANK - OCTOBER 20, 1958	40080010	61
	SUBROUTINE GRT (N,C,IN,IF)	40080020	62
	DIMENSION C(50)	40080030	63
	DO 100 L=1,N	40080040	64
	JK=0	40080050	65
	IF (C(L))45,46,45	40080060	66
45	RT=.9*C(L)	40080070	67
	ASSIGN 1 TO NN	40080080	68
	GO TO 80	40080090	69
1	X0=FPRT	40080100	70
	RT=1.1*C(L)	40080110	71
	ASSIGN 2 TO NN	40080120	72
	GO TO 80	40080130	73
2	X1=FPRT	40080140	74
	RT=C(L)	40080150	75
	ASSIGN 3 TO NN	40080160	76
	GO TO 80	40080170	77
3	X2=FPRT	40080180	78
	GO TO 50	40080190	79
46	RT=-1.0	40080200	80
	ASSIGN 4 TO NN	40080210	81
	GO TO 80	40080220	82
4	X0=FPRT	40080230	83
	RT=1.0	40080240	84
	ASSIGN 5 TO NN	40080250	85
	GO TO 80	40080260	86
5	X1=FPRT	40080270	87
	RT=0.0	40080280	88
	ASSIGN 6 TO NN	40080290	89
	GO TO 80	40080300	90
6	X2=FPRT	40080310	91
50	H=-1.0	40080320	92
	D=-.5	40080330	93
49	DD=1.0+D	40080340	94
	R1=(X0*DD)-(X1*(DD*DD))+(X2*(DD+D))	40080350	95
	DEN=R1*H1-(4.0*X2*(DD*DD))*((X0*DD)-(X1*DD))+X2	40080360	96
	IF (DEN)36,36,51	40080370	97
36	DEN=0.0	40080380	98
51	DEN=SQR(DEN)	40080390	99
53	NN=B1+DEN	40080400	100
	DM=H1-DEN	40080410	101
	IF (ABS(DN)-ABS(DM))57,57,56	40080420	102
56	DEN=DM	40080430	103
	GO TO 58	40080440	104
57	DEN=DM	40080450	105
58	IF (DEN)55,54,55	40080460	106
54	DEN=1.0	40080470	107
55	D1=(-2.0*X2*(DD))/DEN	40080480	108
	H=D1*H	40080490	109
	RT=RT+H	40080500	110
60	IF (ABS(H/RT)-1.0E-6)75,75,60	40080510	111
	ASSIGN 7 TO NN	40080520	112
	GO TO 80	40080530	113
7	IF (ABS(FPRT)-ABS(X2*10.0))62,61,61	40080540	114
61	D1=D1*.5	40080550	115
	H=H*.5	40080560	116
	RT=RT-H	40080570	117
	GO TO 80	40080580	118
62	X0=X1	40080590	119
			120

	X1=X2	W0080600	121
	X2=FPRT	W0080610	122
	D=DI	W0080620	123
	GO TO 49	W0080630	124
75	CALL AUX (RT, FRT)	W0080640	125
76	C(L)=RT	W0080650	126
100	CONTINUE	W0080660	127
	IN=JK	W0080670	128
33	RETURN	W0080680	129
80	JK=JK+1	W0080690	130
	IF (100-JK) 75, 75, 86	W0080700	131
86	CALL AUX (RT, FRT)	W0080710	132
	FPRT=FPRT	W0080720	133
	IF (L-1) 81, 89, 81	W0080730	134
81	DO 82 I=2, L	W0080740	135
	TEM=RT-C(I-1)	W0080750	136
	IF (ABS(TEM)-1.0E-20) 85, 82, 82	W0080760	137
82	FPRT=FPRT/TEM	W0080770	138
89	IF (ABS(FRT)-1.0E-20) 90, 91, 91	W0080780	139
90	IF (ABS(FPRT)-1.0E-20) 76, 91, 91	W0080790	140
91	IF (IF) 33, 84, 33	W0080800	141
84	GO TO NN, (1, 2, 3, 4, 5, 6, 7)	W0080810	142
85	RT=RT+.001	W0080820	143
88	GO TO 80	W0080830	144
	END	W0080840	145
			146
			147
			148
			149
			150
			151
			152
			153
			154
			155
			156
			157
			158
			159
			160
			161
			162
			163
			164
			165
			166
			167
			168
			169
			170
			171
			172
			173
			174
			175
			176
			177
			178
			179
			180

# \*IRFTC AUX

C

AUXILIARY PROGRAM CALLED BY ROOTFINDER SUBROUTINE

C

THIS SUBROUTINE RETURNS CONTROL TO THE ROOTFINDER ROUTINE

## SUBROUTINE AUX(RT, FRT)

EXTERNAL FNC

COMMON/INPUT/U(9), V(5), XK(4), UPPER, XLLOWER, IX, I, PHI, J, AX

598 FORMAT (4H W1=, 1PE15.7, 4H W2=, 1PE15.7)

599 FORMAT (6H XNUM=, 1PE15.7)

600 FORMAT (5H DEN=, 1PE15.7)

601 FORMAT (4H Z1=, 1PE15.7)

602 FORMAT (4H Z2=, 1PE15.7)

603 FORMAT (5H PHI=, 1PE15.7)

604 FORMAT (4H RT=, 1PE15.7)

AX=RT

DIF=.0001

WRITE (6, 804) RT

IF (RT-1.) 25, 28, 35

25 PHI=V(J)-(UPPER-XLOWER)+1.-RT

C ARTIFICIAL VALUE INTENDED TO DRIVE ROOTFINDER TOWARD A ROOT

GO TO 46

28 PHI=V(J)-(UPPER-XLOWER)

GO TO 46

35 CALL RINT2 (U(I), UPPER, DIF, FNC, W1, IND)

CALL RINT2 (XLLOWER, U(I), DIF, FNC, W2, IND)

WRITE (6, 598) W1, W2

XNUM=W1+W2

WRITE (6, 599) XNUM

TOL=D.0001\*XNUM

X=0.0025

5 VALUE=X\*\*((U(I)\*(RT-1.)/(1.-U(I))) \* (1.-X)\*\*(RT-1.))

IF (VALUE.GE.TOL.AND.X.EQ.0.0025) GO TO 50

```

IF (VALUE.LT.TOL.AND.X.EQ.0.0025) GO TO 51
IF (VALUE.LT.TOL) GO TO 39
X=XLOWER-0.1
27 IF (X.LE.0.0) GO TO 50
29 VALUE=X**((0(I)*(RT-1.)/(1.-0(I))) * (1.-X)**(RT-1.))
IF (VALUE.LT.TOL) GO TO 60
X=X-0.1
GO TO 27
32 CALL RINT2 (YLOWER,XLOWER,01F,FNC,Z1,IND)
30 WRITE (6,601) Z1
IF (UPPER.EQ.1.0) GO TO 40
CALL RINT2 (UPPER,1.0,01F,FNC,Z2,IND)
WRITE (6,602) Z2
41 DEN=XNUM+Z1+Z2
WRITE (6,600) DEN
IF (ABS(XNUM).GT.1.E10*DEN) GO TO 3
GO TO 45
40 Z2=0.0
GO TO 41
45 PHI=V(J)-(XNUM/DEN)
GO TO 46
3 PHI=-.001*PI
46 WRITE (6,603) PHI
GO TO 80
39 Z1=0.0
GO TO 30
50 YLOWER=0.0
GO TO 32
51 X=XLOWER
GO TO 5
60 YLOWER=X
GO TO 32
80 FRT=PHI
RETURN
END

```

```

SIMFTE RINT2 LIST 40570010
C INTEGRATION SUBROUTINE WRITTEN BY ROBERT L. MOSLEY 221
C DATE OF WRITE-UP - 2-2-65 40570020
C DATE OF SOURCE DECK - 2-2-65 40570030
C SUBROUTINE RINT2 (A,B,E,FNC,F,IND) 40570040
C ----- 40570050
C 40570060
C A = ONE LIMIT OF THE INTEGRATION. 40570070
C B = OTHER LIMIT OF THE INTEGRATION. 40570080
C E = ERROR BOUND (NON-DIMENSIONAL). 40570090
C FNC = FUNCTION SUBPROGRAM. 40570100
C THE FUNCTION STATEMENT MUST BE - FUNCTION FNC(X) 40570110
C WHERE X IS THE INDEPENDENT VARIABLE. 40570120
C F = THE VALUE OF THE INTEGRAL IS RETURNED HERE. 40570130
C IND = AN INDICATOR WHICH IS RETURNED. 40570140
C ZERO INDICATES THE INTEGRAL DID NOT CONVERGE 40570150
C USING 2**10 INTERVALS. 40570160
C NON-ZERO INDICATES THE INTEGRAL CONVERGED WITHIN 40570170
C THE ERROR BOUND. 40570180
C 40570190
C DOUBLE PRECISION F(31),AA,4H,SIGMA,FNC,HO,PI,P,FMIN,R,FF,AMS,44C,DA 240

```

141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240

185	EMIN=10000000.	40570210	241
	AA=A		242
	BB=B		243
	HO=BB-AA		244
	T=.5*(FNC(AA)+FNC(BB))*HO		245
	P=1.	40570240	246
	DO 100 I=1,12		247
	SIGMA=0.		248
	Q=1.	40570260	249
	P=P*2.	40570270	250
10	CONTINUE	40570280	251
	SIGMA=SIGMA+FNC(AA+(HO*Q)/P)	40570290	252
	Q=Q+2.		253
	IF (Q,LT,P) GO TO 10	40570310	254
	T(I+1)=(SIGMA*HO)/P+.5*T(I)	40570320	255
	FF=T	40570330	256
	A4K=1.		257
	DO 20 J=1,I	40570350	258
	L=I-J+1	40570360	259
	A4K=A4K*4.	40570370	260
	T(L)=T(L+1)+(T(L+1)-T(L))/(A4K-1.)	40570380	261
20	CONTINUE	40570390	262
C	WRITE (6,99) (T(K),K=1,I)	40570400	263
99	FORMAT (1P8.015,7/H015.7)	40570410	264
	I2=I+1		265
	R=FF-T	40570420	266
	IF (DABS(T).GT.1.0-10) R=R/T		267
	EMIN=DABS(R)		268
	ANS=T	40570470	269
90	IF (DABS(R).LE.E.AND.1.GT.3) GO TO 200		270
100	CONTINUE	40570490	271
C	I=I-1	40570500	272
200	IND=15-1	40570510	273
	WRITE (6,98) EMIN		274
98	FORMAT (1P015.7)		275
	PAUSE	40570530	276
	RETURN	40570540	277
	END	40570550	278
			279
			280
			281
			282
			283
			284
			285
			286
			287
			288
			289
			290
			291
			292
			293
			294
			295
			296
			297
			298
			299
			300
			301
			302
			303
			304
			305
			306
			307
			308
			309
			310
			311
			312
			313
			314
			315
			316
			317
			318
			319
			320
			321
			322
			323
			324
			325
			326
			327
			328
			329
			330
			331
			332
			333
			334
			335
			336
			337
			338
			339
			340
			341
			342
			343
			344
			345
			346
			347
			348
			349
			350
			351
			352
			353
			354
			355
			356
			357
			358
			359
			360
			361
			362
			363
			364
			365
			366
			367
			368
			369
			370
			371
			372
			373
			374
			375
			376
			377
			378
			379
			380
			381
			382
			383
			384
			385
			386
			387
			388
			389
			390
			391
			392
			393
			394
			395
			396
			397
			398
			399
			400
			401
			402
			403
			404
			405
			406
			407
			408
			409
			410
			411
			412
			413
			414
			415
			416
			417
			418
			419
			420
			421
			422
			423
			424
			425
			426
			427
			428
			429
			430
			431
			432
			433
			434
			435
			436
			437
			438
			439
			440
			441
			442
			443
			444
			445
			446
			447
			448
			449
			450
			451
			452
			453
			454
			455
			456
			457
			458
			459
			460
			461
			462
			463
			464
			465
			466
			467
			468
			469
			470
			471
			472
			473
			474
			475
			476
			477
			478
			479
			480
			481
			482
			483
			484
			485
			486
			487
			488
			489
			490
			491
			492
			493
			494
			495
			496
			497
			498
			499
			500
			501
			502
			503
			504
			505
			506
			507
			508
			509
			510
			511
			512
			513
			514
			515
			516
			517
			518
			519
			520
			521
			522
			523
			524
			525
			526
			527
			528
			529
			530
			531
			532
			533
			534
			535
			536
			537
			538
			539
			540
			541
			542
			543
			544
			545
			546
			547
			548
			549
			550
			551
			552
			553
			554
			555
			556
			557
			558
			559
			560
			561
			562
			563
			564
			565
			566
			567
			568
			569
			570
			571
			572
			573
			574
			575
			576
			577
			578
			579
			580
			581
			582
			583
			584
			585
			586
			587
			588
			589
			590
			591
			592
			593
			594
			595
			596
			597
			598
			599
			600
			601
			602
			603
			604
			605
			606
			607
			608
			609
			610
			611
			612
			613
			614
			615
			616
			617
			618
			619
			620
			621
			622
			623
			624
			625
			626
			627
			628
			629
			630
			631
			632
			633
			634
			635
			636
			637
			638
			639
			640
			641
			642
			643
			644
			645
			646
			647
			648
			649
			650
			651
			652
			653
			654
			655
			656
			657
			658
			659
			660
			661
			662
			663
			664
			665
			666
			667
			668
			669
			670
			671
			672
			673
			674
			675
			676
			677
			678
			679
			680
			681
			682
			683
			684
			685
			686
			687
			688
			689
			690
			691
			692

C PROGRAM 2 BETA PRIOR, MEAN ESTIMATED

SUBFC MEAN REF  
C PARAMETERS OF BETA PRIOR A, 4  
C A = 40/(1-0)  
C R = ROOT  
C U = MEAN, OR AVERAGE VALUE OF THE PROBABILITY THAT A SYSTEM WORKS  
C ALL OTHER VARIABLES ARE DEFINED AS IN PROGRAM 1

C(continued) Z=INPUT(0(9),V(5),X(4),UPPER,XLOWER,IX,I,PHI,J

850 FORMAT (I2)  
900 FORMAT (6F10.4)  
901 FORMAT (5F5.2)  
902 FORMAT (4F5.3)  
903 FORMAT(F5.1)  
870 FORMAT (F10.4,2(5X,F5.3),2(5X,F10.3),5X,F10.8)  
READ (5,850) II  
READ (5,850) JJ  
READ (5,850) KK  
READ (5,900) (U(I),I=1,II)  
READ (5,901) (V(J),J=1,JJ)  
READ (5,902) (X(K),K=1,KK)  
READ (5,903) TX  
A=1  
Im=20  
I=0  
DO 600 K=1,KK  
DO 599 I=1,II  
DO 598 J=1,JJ  
TEST=U(I)\*(1.+X(K))  
UPPER=AMIN1(1.,TEST)  
25 XLOWER=U(I)\*(1.-X(K))  
CALL GRT (U,IX,Im,IF)  
A=(U(I)\*TX)/(1.-U(I))  
WRITE (6,870) U(I),V(J),X(K),A,IX,PHI  
598 CONTINUE  
599 CONTINUE  
600 CONTINUE  
CALL EXIT  
END

C GENERAL ROOT FINDER FOLLOWS AS ABOVE

C AUXILIARY SUBROUTINE FOLLOWS AS ABOVE

C INTEGRATION ROUTINE FOLLOWS AS ABOVE

301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360



	361
	362
	363
	364
	365
SINHTC FNC	366
C	367
C	368
DOUBLE PRECISION FUNCTION FNC(X)	369
COMMON/INPUT/0(9),V(5),X(4),UPPER,XLOWER,IX,1,PHI,J,AX	370
FNC=X**(((0(1)*AX)-1.0)/(1.0-0(1)))*(1.00-x)**(AX-1.0)	371
4 RETURN	372
END	373
	374
	375
SENTRY	376
MEAN	377
	378
	379
	380
	381
C	382
PROGRAM 3	383
GAMMA PRIOR, MTR ESTIMATED	384
	385
SINHTC ROUT-2	386
	387
C	388
C	389
C	390
	391
C	392
C	393
COMMON/INPUT/V(9),X(3),J,K,H,THETA	394
900 FORMAT (I2)	395
901 FORMAT (9F5.2)	396
910 FORMAT (F6.2,5X,F5.2,5X,F10.7,5X,F10.7)	397
READ (5,900) JJ	398
READ (5,900) KX	399
READ (5,901) (V(J),J=1,JJ)	400
READ (5,901) (X(K),K=1,KK)	401
N=1	402
IF=0	403
DO 599 K=1,KK	404
H=1.0	405
DO 600 J=1,JJ	406
CALL GRT (N,H,IN,IF)	407
WRITE (6,910) V(J),X(K),H,THETA	408
600 CONTINUE	409
599 CONTINUE	410
CALL EXIT	411
END	412
	413
	414
	415
C	416
ROUTINDER SUBROUTINE FOLLOWS AS ABOVE	417
	418
	419
	420

SINFTC AUX		421
SUBROUTINE AUX (RT,FRF)		422
COMMON/INPUT/V(9),XX(3),J,K,H,THETA		423
799 FORMAT (4HRT=,F10.7)		424
800 FORMAT (10X,F12.8)		425
801 FORMAT (5X,F12.8)		426
802 FORMAT (26HODENOMINATOR TOO NEAR ZERO)		427
803 FORMAT (3(5X,F12.8))		428
WRITE (6,799) RT		429
IF (RT.LE.0.) GO TO 5		430
IF (RT.GE.20.0) GO TO 10		431
R=RT*XX(K)		432
Z=GAMMA (RT,K)		433
WRITE (6,800) Z		434
Y=GAMMA (RT,0.)		435
WRITE (6,801) Y		436
IF (Y.EQ.0.) GO TO 3		437
THETA=V(J)-(Z/Y)		438
WRITE (6,803) THETA,Z,Y		439
GO TO 4		440
3 WRITE (6,802)		441
5 THETA = V(J)-1.0+RT		442
C     ARTIFICIAL VALUE INTENDED TO DRIVE ROOT-FINDER TOWARD A ROOT		443
GO TO 4		444
10 THETA=-1.0-20.0*RT		445
4 FRF=THETA		446
RETURN		447
END		448
		449
		450
		451
		452
C     NYU GAMM (FAP CODED ROUTINE) FOLLOWS		453
C     SHARE PROGRAM (NYU GAMM, 3218) IS CALLED BY AUXILIARY ROUTINE		454
		455
		456
		457
		458
SENTRY     R001-2		459

REFERENCES

1. Drenick, R. F., "The Failure Law of Complex Equipment," J. Soc. Ind. Appl. Math., 8, pp. 680-690, 1960.
2. Feeney, G. J., J. W. Petersen, and C. C. Sherbrooke, An Aggregate Base Stockage Policy for Recoverable Spare Parts, The RAND Corporation, RM-3644-PR (DDC No. AD 408943), May 1963.
3. Pearson, Karl (ed.), Tables of the Incomplete Beta-Function, Biometrika, London, 1934.
4. -----, Tables of the Incomplete  $\Gamma$ -Function, Biometrika, London, 1946 (originally issued 1922).
5. Raiffa, Howard, and Robert Schlaifer, Applied Statistical Decision Theory, Harvard University Press, Boston, 1961.
6. Yaglom, A. M., An Introduction to the Theory of Stationary Random Functions, Prentice-Hall, Inc., Englewood Cliffs, New Jersey, 1962.



August 1966

RB-5084

RM-5084-NASA, A Bayesian Approach to Reliability Assessment,  
B. L. Fox, RAND Memorandum, August 1966, 30 pp.

PURPOSE: To specify the parameters of a prior distribution for two cases: the reliability of a unit that either performs satisfactorily throughout a mission or does not, and the failure rate of a unit that fails according to the exponential distribution. Prediction of demand for spares is considered in each case.

SCOPE: Bayesian analysis is an obvious approach to estimating reliability parameters from such mixed data sources as test results, information on analogous components, and engineering estimates. The prior distribution, of necessity subjective, is ideally based solely on the latter two sources. This study gives a method for specifying the parameters of the prior distribution, requiring only information corresponding to the most likely value of reliability, and to the subjective odds that the error in this estimate is less than a given percentage. Testing data are then merged with the prior distribution via Bayes rule to obtain a posterior distribution. Roughly speaking, the spread of the prior distribution is inversely proportional to the degree of prior belief and determines how heavily the distribution will be weighted when it is combined with test data. Tables of the parameters of the prior distribution, computed according to the method described, appear in the Appendix.

BACKGROUND: This research was done by RAND for the National Aeronautics and Space Administration in connection with the Apollo mission reliability assessment study. It should be of interest to those working on reliability estimation, allocation of investment among system components to achieve maximum system reliability, and stockage applications.

